

MODEL	OUTPUT			FUEL USE			DESIGN PRESSURE		DIMENSIONS (MM)			FLUE DIAM	FEED WATER INLET	MAIN STEAM OUTLET	BLOW DOWN OULET	SIZE	SAFETY VALVES QTY
	KW	H/P	KG/H	NAT GAS / LPG MJ/HR	L/H	L/H	KPA	PSI	HEIGHT	FLOOR L	FLOOR W						
CBW3	30	3	47	133	5.2	3.5	1000	145	1650	950	750	125	15	15	20	20	1
CBW5	50	5	78	222	8.8	5.8	1000	145	1800	950	750	150	15	20	20	20	1
CBW7.5	75	7.5	117	332	13.1	8.7	1000	145	1900	1030	820	150	15	20	20	20	1
CBW10	100	10	155	443	17.1	11.6	1000	145	2000	1030	820	150	15	20	20	20	1
CBW15	150	15	233	665	26.2	17.4	1000	145	2250	1200	950	150	20	25	20	20	1
CBW20	200	20	310	886	34.9	23.2	1000	145	2600	1500	1200	200	20	25	20	20	1
CBW25	250	25	388	1108	43.6	29	1000	145	2700	1500	1200	200	20	32	20	20	1
CBW30	300	30	465	1329	52.3	34.8	1000	145	2800	1500	1200	200	25	40	20	20	1
CBW40	400	40	620	1772	69.8	46.4	1000	145	3050	1900	1500	250	25	40	20	25	1
CBW50	500	50	775	2215	83.3	58	1000	145	3200	1900	1500	250	25	50	20	25	1
CBW75	750	75	1163	3323	130.8	87	1000	145	3500	2450	2000	300	25	50	32	25	2
CBW100	1000	100	1550	4430	170.5	116	1000	145	4300	2450	2000	300	25	65	32	32	2
CBW1500	1500	150	2325	6645	253.7	174	1000	145	4600	3000	2500	350	25	80	40	32	2

